



Gulf ATF MV

Premium quality Automatic Transmission Fluid

Product Description

Gulf ATF MV is premium quality automatic transmission fluid for all Ford and General Motors automatic transmissions requiring MERCON® V or DEXRON®-III quality fluids respectively. The advanced additive technology and premium quality base oils used in this oil provide excellent oxidation resistance, wear protection, friction durability and seal compatibility. It is designed to exceed the performance requirements of Ford MERCON® V and General Motors DEXRON® III specifications. It also meets the performance requirements of Allison Transmission Division's C-4 specification.

Features & Benefits

- Excellent thermo-oxidative stability, wear protection and resistance to chemical deterioration leads to longer fluid and transmission life
- Controlled frictional properties lead to smooth shift performance, efficient transmission of power and eliminates shudder often encountered in transmissions with continuously slipping torque converters
- Extremely high Viscosity index ensures adequate lubrication in both high operating & low starting temperatures
- Provides excellent protection against rust and corrosion
- Superior foam control leads to smooth & lasting shift feel and reduces fluid loss
- Improved low temperature fluidity leads to easy pumping in the hydraulic circuits
- Superior seal compatibility ensures longer seal life and reduces possibility of oil leakage

Applications

- Recommended for all vehicles of Ford requiring MERCON® V quality fluids and General Motors requiring DEXRON®-III quality fluids.
- Being back serviceable, also recommended for automatic transmissions requiring Ford MERCON® V or General Motors DEXRON® II E or DEXRON® II D fluids and also for imported cars like Audi, Honda, Mazda, Nissan, Opel, Renault, Toyota and Volkswagen where such fluids are specified
- Also recommended for Allison Powershift transmissions or other torque converters requiring Allison C-4 quality fluids.

Specifications, Approvals & Typical Properties

Meets the following Specifications		
Ford MERCON® V, Ford MERCON®		
General Motors DEXRON® III		
ZF TE-ML 14B, 16L & 17C		
MAN 339 Typ F		
Voith 55.6335.xx (standard drain)		
Allison Transmission Division's C-4		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	7.0
Viscosity Index	D 2270	169
Flash Point, °C	D 92	206
Pour Point, °C	D 97	-45
Brookfield Viscosity @ -40 °C, cP	D 2983	11800
Density @ 15°C, Kg/l	D 1298	0.858

DEXRON® is a registered trademark of General Motors Corporation.

MERCON® is a registered trademark of Ford Motor Company

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.