



# Gulf ATF MX

## Premium quality Steering Fluid

### Product Description

**Gulf ATF MX** is a premium fluid specifically designed for mechanical and power steering of passenger cars, commercial vehicles and cross country vehicles. The product is formulated using highly refined base oil and advanced additive technology to provide excellent oxidation resistance, wear protection, friction durability and seal compatibility. It is suitable for use in mechanical and power steering applications requiring Mercedes Benz MB 236.3 quality oils. It is also suitable for automatic transmissions of vehicles requiring fluids meeting General Motors DEXRON® II. It meets various ZF specifications.

### Features & Benefits

- Excellent thermo-oxidative stability, wear protection and resistance to chemical deterioration leads to longer fluid and equipment life
- The low viscosity makes them ideal for use in steering systems which are characterised with a low fluid volume and high flow rates.
- Extremely high Viscosity index ensures adequate lubrication in both high operating & low starting temperatures
- Provides excellent protection against rust and corrosion
- Superior foam control leads to smooth & lasting shift feel and reduces fluid loss
- Improved low temperature fluidity leads to easy pumping in the hydraulic circuits of steering and Automatic Transmissions and reduces the risk of cavitation in the pumps.

### Applications

- Mechanical and power steering of passenger cars, commercial vehicles and cross country vehicles.
- Mechanical and power steering of MB requiring MB 236.3 quality fluids.
- Automatic Transmission and Power/ Manual steering of ZF requiring ZF TE-ML 03D, 04D, 09, 11, 14A, 17C type fluids.
- General Motors Automatic Transmissions requiring DEXRON®-II quality fluids.
- Hydraulic fan drives for auxiliary radiator

### Specifications, Approvals & Typical Properties

Meets the following Specifications		
General Motors DEXRON® II		
ZF TE-ML 03D, 04D, 09, 11, 14A, 17C		
Voith G 607 (D 55 6335.xx)		
Has the following Approvals		
Daimler MB 236.3		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	6.92
Viscosity Index	D 2270	162
Flash Point, °C	D 92	202
Pour Point, °C	D 97	-45
Brookfield Viscosity @ -40 °C, cP	D 2983	39790
Density @ 15°C, Kg/l	D 1298	0.870

DEXRON® is a registered trademark of General Motors Corporation.

December 2007

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

[www.gulfoilltd.com](http://www.gulfoilltd.com)