



Gulf Dieselmotive 473

Zinc-free railroad engine oil

Product Description

Gulf Dieselmotive 473 is zinc-free oil specially designed for railroad diesel locomotive engines. It is formulated with carefully selected additives to provide excellent detergency, dispersancy, good filterability, excellent oxidation stability and ins service TBN retention. The zinc-free formulation technology used in this oil makes it suitable for lubrication of engines with silver alloy bearings also. It is available in SAE 40 viscosity grade and exceeds the performance requirements of Locomotive Maintenance Officers Association (LMOA) Generation 4 and API CF/CF-2.

Features & Benefits

- Excellent detergency/dispersancy provides superior engine cleanliness
- Excellent in-service retention of TBN facilitates extended drain intervals
- High oxidation stability minimizes sludge and deposit formation
- Zinc-free formulation protects silver bearings against corrosion

Applications

- Railroad diesel locomotive engines of Electromotive Division (EMD), General Electric (GE) and American Locomotive Company (ALCO) specifying LMOA Generation 4 oils
- Marine and stationary engines for power generation or off-shore drilling requiring zinc-free oils
- Detroit Diesel 149 series engines operating under severe conditions
- Stationary engines requiring API CF and CF-2 quality oils

Specifications, Approvals & Typical Properties

Meets the following Specifications		
LMOA Generation 4		
API CF, CF-2		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	15.0
Viscosity Index	D 2270	97
Flash Point, °C	D 92	246
Pour Point, °C	D 97	-18
TBN, mg KOH/g	D 2896	13.3
Density @ 15°C, Kg/l	D 1298	0.901
Sulphated Ash, %wt	D 874	1.60
Zinc, ppm	ICP	< 10

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.