



Gulf Fidelity LL

Long Life Air Compressor Lubricant

Product Description

Gulf Fidelity LL series are long life ashless air compressor lubricants developed for use in rotary compressors of screw or vane design, reciprocating compressors and centrifugal compressors to provide long and reliable service in extreme temperatures and severe operating conditions. Gulf Fidelity LL is manufactured from specially selected base fluids and advanced additive technology to provide excellent thermo-oxidative stability, resistance to sludge & varnish formation and wear protection similar to synthetic products meeting SAE M1003-2 specification.

Features & Benefits

- Outstanding thermo-oxidative stability and excellent anti-wear protection leads to longer oil and equipment life
- Low sludge, varnish and carbon forming tendency help in reducing maintenance cost
- High viscosity index coupled with excellent low temperature fluidity makes these oils suitable for use in wide operating temperature range
- Zinc-free formulation ensures excellent filterability by minimizing oil filter blockage in wet condition
- Excellent low volatility characteristics give low oil consumption and reduced top-up rates
- Improved surface properties results in very good anti-foaming and air release properties and superior demulsibility
- Offers excellent protection against rust and corrosion
- Compatible with mineral lubricants and also with seals and paints normally used with mineral oils.

Applications

- Single or multiple stage rotary screw or vane, centrifugal compressors and reciprocating compressors of various OEMs including Hydrovane, Sullair, Atlas Copco, CompAir and others.
- The formulation has undergone a successful field trial in Sullair Model 12-50H Screw Compressor (50 HP, 1780 rpm, air discharge temperature 93°C) for 8502 hrs and in Hydrovane HV04-HV07 air compressors (air discharge temperature 120°C) for 2450 hrs.
- Compressors used in mobile and stationary applications.

Specifications, Approvals & Typical Properties

Meets the following Specification		32	46	68	100	150
DIN 51506 VDL		x	x	x	x	x
ISO 6743-3 ISO-L-DAB and ISO-L-DAJ		x	x	x	x	x
Typical Properties						
Test Parameters	ASTM Method	Typical Values				
Viscosity @ 40 °C, cSt	D 445	32.5	46.1	68.3	100.9	144
Viscosity Index	D 2270	128	130	136	138	135
Flash Point, °C	D 92	220	222	222	234	220
Pour Point, °C	D 97	-36	-36	-36	-36	-36
Density @ 15°C, Kg/l	D 1298	0.848	0.852	0.854	0.858	0.864
Air Release, @ 50°C minutes	D 3427	2	5	8	12	12
RBOT, minutes	IP 229	1718	1744	2066	2008	2065
Rust Test	D 665 A/B	Pass	Pass	Pass	Pass	Pass
Emulsion Test 30 minutes max	@ 54 oC	Pass	Pass	Pass	-	-
	@ 82 oC	-	-	-	Pass	Pass
Foam (aft 10 mins of settling - all seq)	D 892	Nil	Nil	Nil	Nil	Nil
FZG, fail load stage	DIN 51354 Part II	>12	>11	>12	>12	>12

October 2013

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.