



Gulf Formula FE

Passenger Car Motor Oil

Product Description

Gulf Formula FE is the most advanced fuel economy passenger car motor oil formulated from synthetic base stocks and state-of-the-art additive technology to provide outstanding protection against wear and deposits & sludge build-up. It is available in two different viscosity grades viz. SAE 0W-30 & SAE 5W-30. SAE 0W-30 grade is particularly developed for the latest VW and Audi vehicles with long life service (WIV) for flexible oil drain intervals. It has been exclusively designed to exceed the stringent requirements of Volkswagen standard VW 506 01 and is recommended for use in direct injection diesel engines with pump injectors. SAE 5W-30 grade is developed to exceed the service fill requirements of most recent models of Ford.

Features & Benefits

- Outstanding thermo-oxidative stability decelerates oil degradation and thus facilitates extended oil change intervals
- Low HTHS (High Temperature High Shear) viscosity and special friction modifying agents facilitate fuel economy retention for extended service life
- Reduced deposits and sludge build-up in engine and turbocharger ensures rated power and torque
- Excellent antiwear technology leads to superior wear protection
- Exceptional Stay-in-Grade performance ensures reliable lubrication even at higher load and operating temperatures
- Outstanding low temperature fluidity aids quick cold start and provides wear protection at start-up

Applications

- Recommended for passenger cars and light duty vehicles powered by gasoline and diesel engines specifically designed to be capable of using low friction low viscosity oils
- SAE 0W-30 is recommended for all the latest, turbocharged, multi valve, direct injection gasoline and diesel engines in modern passenger cars of VW and Audi including the direct injection diesel engines equipped with pump injectors requiring oils meeting VW 503 00, VW 506 00 & VW 506 01 standards
- SAE 5W-30 is recommended for the latest models of Ford vehicles requiring Ford M2C 913-A & 913-B quality oils

Specifications, Approvals & Typical Properties

| Meets the following Specifications | | 0W-30 | 5W-30 |
|------------------------------------|-------------|----------------|-------|
| VW 503 00, 506 00, 506 01 | | X | |
| Ford M2C 913-A | | | X |
| Ford M2C 913-B | | | X |
| Typical Properties | | | |
| Test Parameters | ASTM Method | Typical Values | |
| Viscosity @ 100 °C, cSt | D 445 | 9.60 | 10.80 |
| Viscosity Index | D 2270 | 167 | 162 |
| Flash Point, °C | D 92 | 222 | 220 |
| Pour Point, °C | D 97 | -39 | -39 |
| Density @ 15°C, Kg/l | D 1298 | 0.860 | 0.861 |

May 2015

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com