



Gulf Formula PCX Plus

Catalyst Compatible Fully Synthetic Passenger Car Oil

Product Description

Gulf Formula PCX Plus is the most advanced high performance passenger car motor oil formulated from synthetic base stocks and latest additive technology to provide fuel savings and to prolong the life & maintain the efficiency of emission reducing systems. It is fully compatible with Diesel Particulate Filter (DPF) and Gasoline Three Way Catalyst (TWC). It is specially developed for PSA Peugeot Citroën vehicles requiring latest B71 2290 specification and other OEMs requiring ACEA C2 type of oils.

Features & Benefits

- Mid SAPS (Sulphated Ash Phosphorus Sulphur) oil formulation prolongs the life and maintains the efficiency of DPF and TWC
- Outstanding thermo-oxidative stability resists oil degradation and thus facilitates extended oil change intervals
- Active cleaning agents reduce deposits & sludge and keeps engine clean
- Enhanced frictional properties provide improved fuel economy (ACEA C2) compared to mineral engine oils
- Excellent antiwear technology leads to superior wear protection
- Exceptional Stay-in-Grade performance ensures reliable lubrication even at higher loads & operating temperatures
- Outstanding low temperature fluidity aids quick cold start and provides wear protection at start-up

Applications

- Suitable for use in latest generation passenger cars, SUV's and light vans of Peugeot and Citroën requiring oils meeting latest PSA Peugeot Citroën B71 2290 specification
- Modern high performance gasoline and diesel engines in passenger cars and light duty vehicles fitted with DPF and TWC requiring catalyst compatible fuel economy oils meeting ACEA C2 specifications
- These oils may be unsuitable for use in some engines (consult owner manual/ handbook)

Specifications, Approvals & Typical Properties

Meets the following Specifications		5W-30
ACEA C2		X
PSA Peugeot Citroën B71 2290		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	10.2
Viscosity Index	D 2270	175
Flash Point, °C	D 92	232
Pour Point, °C	D 97	-42
Density @ 15°C, Kg/l	D 1298	0.851
Sulfated Ash, % wt	D 874	0.54
Phosphorus, % wt	D 4047/ICP	0.078

April 2020

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.