



Gulf Formula Racing

Synthetic Passenger Car Motor Oil

Product Description

Gulf Formula Racing series are advanced high performance synthetic passenger car engine oil formulated from finest quality synthetic base stocks and state-of-the-art additive technology. It has been specially developed for all modern turbocharged, high output gasoline engines and some diesel engines of cars used in high performance cars as well as SUVs, light vans and trucks. It is designed to provide excellent engine cleanliness and wear protection for the entire drain interval.

Features & Benefits

- Outstanding thermo-oxidative stability reduces deposits & sludge build-up and facilitates extended oil and engine life
- Superior antiwear technology provides excellent wear protection under all conditions
- Active cleaning agents ensure maximum engine cleanliness resulting in trouble free engine operation
- Excellent low temperature fluidity aids quick cold start and provides wear protection at start-up
- Effective Stay-in-grade performance ensures reliable lubrication even at higher load and operating temperatures
- Exceptionally high viscosity index ensures right oil film even at high operating temperatures encountered in driving conditions similar to racing

Applications

- High performance, turbo-charged, super charged, naturally aspirated, multi valve gasoline powered cars, SUVs & Light Duty Vehicles.

Specifications, Approvals & Typical Properties

| Meets the following Specifications | | 5W-50 | 10W-50 | 10W-60 |
|------------------------------------|-------------|----------------|--------|--------|
| ACEA A3/B4 | | | X | X |
| API SN | | X | X | |
| Typical Properties | | | | |
| Test Parameters | ASTM Method | Typical Values | | |
| Viscosity @ 100 °C, cSt | D 445 | 17.3 | 17.7 | 22.3 |
| Viscosity Index | D 2270 | 185 | 165 | 168 |
| Flash Point, °C | D 92 | 233 | 236 | 238 |
| Pour Point, °C | D 97 | -36 | -36 | -33 |
| TBN, mg KOH/g | D 2896 | 10.0 | 10.1 | 10.3 |
| Density @ 15°C, Kg/l | D 1298 | 0.8456 | 0.8482 | 0.8462 |
| Sulphated Ash, %wt | D 874 | 1.10 | 1.20 | 1.12 |

September 2019

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.