



Gulf GEARTEK WT

High performance Industrial Gear Oil

Product Description

Gulf GEARTEK WT series are high performance extreme pressure oils designed for lubrication of heavy-duty industrial gears. These are formulated with high quality mineral base oils along with specially selected additive technology to provide excellent load carrying capacity even under extreme conditions including shock loading. These heavy-duty Industrial gear oils provide excellent protection against scuffing and resistance against micro-pitting in the gear boxes under wide operating temperature range and meets latest Flender specifications.

Features & Benefits

- Excellent load carrying and anti-friction characteristics reduce gear tooth and bearing wear.
- Good oxidation and thermal stability help withstand high thermal loading and keeping system clean by resisting sludge built up.
- Excellent micro-pitting performance to reduce the risk of premature failure due to surface distress.
- Special additive technology helps in clean gear performance under condition of high temperature and oxidation.
- Protects system from rust and corrosion even in presence of water contamination
- Compatible with generally used inside gear box paints and standard sealing materials.

Application

- Heavy duty Industrial gear transmissions requiring EP performance.
- Circulating and splash lubricated systems
- Steel gear transmissions.
- Recommended for use in gear boxes that require lubricants meeting Flender specification.

Note:

1. While changing the gear oil, drain off the previous oil completely and inspect internally. Flush the gear box with fresh Gulf GEARTEK WT. Drain the flushed oil and then fill with fresh Gulf GEARTEK WT. For complete benefit, Gulf GEARTEK WT should not be mixed with other lubricants.
2. Not recommended for use in automotive hypoid gears.

Specifications, Approvals & Typical Properties

Meets the following Specifications		VG 1000
DIN 51517 Part 3 CLP, AGMA 9005-E02 (EP)		X
Flender FVA 54/7, AIST 224		X
Siemens Revision 16 for Flender gear units		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 40 °C, cSt	D 445	1000
Viscosity Index	D 2270	105
Flash Point, °C	D 92	265
Density @ 15°C, Kg/l	D 1298	0.9057
Pour Point	D 97	-6
Copper Corrosion (3 hour @100 °C)	D 130	1b
FZG scuffing load stage (A/8.3/90)	D 4048	>14

Dec 2025

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com