

# Gulf MAX Ultra Pick-up Synthetic Technology Diesel Engine Oil for Pick-ups

### **Product Description**

**Gulf MAX Ultra Pick-up** is a high performance Diesel Engine oil designed intended for the modern high performance light-duty diesel engines in pick-up trucks. It provides all-round engine protection to ensure trouble-free operation even under difficult driving conditions, and also offers fuel economy benefits. Gulf MAX Ultra Pick-up is suitable for a variety of light-duty diesel engine types such as common rail direct injection (CRDI), turbocharged, naturally aspirated and multivalve type engines.

#### Features & Benefits

- Improved oxidation stability reduces sludge build up & viscosity increase to facilitate long drain intervals
- Enhanced detergency minimises deposits and enhances engine cleanliness
- · Good soot handling capacity helps control oil thickening and wear
- · Improved fuel economy benefits
- · Better wear protection reduces maintenance costs and extends engine life
- Good corrosion inhibition properties provide protection against rust and corrosion

#### Application

- Modern high performance, multivalve, common rail direct injection (CRDI), turbocharged, or naturally aspirated light-duty diesel engines of pick-up trucks for arduous conditions such as city stop and go, high speed and/ or high load, including those equipped with Exhaust Gas Recirculation (EGR)
- Also suitable for light-duty diesel engines in MUVs and SUVs requiring such type of oils

NOTE: Not suitable for vehicles employing Diesel Particulate Filter (DPF) and requiring low SAPS oil.

## **Specifications, Approvals & Typical Properties**

| Meets the following Specifications API CI-4 |             | 10W-30         |
|---|-------------|----------------|
|   |             | X              |
| Typical Properties                          |             |                |
| Test Parameters                             | ASTM Method | Typical Values |
| Viscosity at 100 °C, cSt                    | D 445       | 12.3           |
| Viscosity Index                             | D 2270      | 144            |
| Flash Point, ºC                             | D 92        | 236            |
| Pour Point, °C                              | D 97        | -42            |
| TBN, mg KOH/g                               | D 2896      | 10.6           |
| Density @ 15°C, Kg/l                        | D 1298      | 0.8712         |
| Sulphated Ash, wt%                          | D 874       | 1.31           |

Gulf Asia-Pacific - July 2025

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language

version shall prevail. www.gulfoilltd.com