



# Gulf MAX Ultra + Pick-up

## Synthetic Technology Diesel Engine Oil

### for Pick-ups

#### Product Description

**Gulf MAX Ultra + Pick-up** is a high-performance Diesel Engine oil designed for the modern light-duty diesel engines, especially those in pick-up trucks. It meets the requirements of most Japanese, European and North American OEMs. It provides all-round engine protection to ensure trouble-free operation even under difficult driving conditions and offers fuel economy benefits (SAE 10W-30). Gulf MAX Ultra + Pick-up is suitable for a variety of light-duty diesel engine types such as Common Rail Direct Injection (CRDI), turbocharged, naturally aspirated and multivalve type engines.

#### Features & Benefits

- High oxidation stability reduces sludge build up & viscosity increase to facilitate long drain intervals
- Improved detergency minimises deposits and enhances engine cleanliness
- Better soot handling capacity helps control oil thickening and wear
- Enhanced wear protection reduces maintenance costs and extends engine life
- Good corrosion inhibition properties provide protection against rust and corrosion

#### Application

- Latest high performance low emission diesel engines in pick-up trucks including those equipped with DPF and Exhaust Gas Recirculation (EGR). Also suitable for use in vehicles requiring API CJ-4 / CI-4 Plus / CI-4 or earlier generation oils
- Also suitable for light-duty diesel engines in MUVs and SUVs, or heavy-duty trucks requiring such type of oils

#### Specifications, Approvals & Typical Properties

Meets the following Specifications		10W-30	10W-40
API CK-4/SN, ACEA E11		X	X
Volvo VDS-4.5/ Mack EOS-4.5/ Renault Trucks RLD-3		X	X
Daimler 15C100 (228.31), MTU Type 2.1, Cummins CES 20086		X	X
DQC III-18 LA, DDC 93K222, Cat ECF-3, MAN M3775		X	X
Ford WSS-M2C171-F1			X
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity at 100 °C, cSt	D 445	12.3	15.4
Viscosity Index	D 2270	145	156
Flash Point, °C	D 92	230	220
Pour Point, °C	D 97	-42	-39
TBN, mg KOH/g	D 2896	11.0	10.0
Density @ 15°C, Kg/l	D 1298	0.8873	0.8870
Sulphated Ash, wt%	D 874	0.99	0.99

Gulf Asia-Pacific – July 2025

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

[www.gulfoilltd.com](http://www.gulfoilltd.com)