



# Gulf Merit

## Premium oil for pneumatic rock drill and tool lubrication

### Product Description

**Gulf Merit** series are premium quality oils specially developed for the lubrication of pneumatically operated rock drills and other air operated percussion tools. These oils are blended from high quality mineral oils and unique combination of superior film strength, tackiness and anti-wear additives. These oils provide excellent chemical stability and protection against wear, rust and corrosion. These oils have good adhesiveness and preferential metal wetting properties that maintain continuous oil film even in presence of water and thereby reduce the negative effects of water, condensed from moisture carried along with the air stream, on wear and corrosion. The combination of these properties along with superior EP characteristics help in providing excellent lubrication leading to long component life. They are available in five ISO viscosity grades viz. ISO VG 46, 100, 150, 220 and 320.

### Features & Benefits

- Excellent load carrying capacity and anti-wear protection reduce component wear and prolong equipment life
- Good chemical stability minimises sludge and deposit formation
- Superior metal wetting properties and adhesiveness help adhesion to metal surfaces and protect them from corrosion
- Excellent water emulsification property provides adequate lubrication even in presence of water

### Applications

- Pneumatically operated rock drills in underground/surface mining operations and quarry operations
- Pneumatically operated drills and jack hammers in construction of roads and buildings
- Wide variety of heavy-duty pneumatically operated equipment
- Percussion and rotary air-operated tools in industrial operations
- Pneumatic equipment of Gardner Denver, Chicago Pneumatic, Ingersoll-Rand and other manufacturers

### Specifications, Approvals & Typical Properties

ISO Viscosity grades		46	100	150	220	320
<b>Typical Properties</b>						
Test Parameters	ASTM Method	Test Values				
Viscosity @ 40 °C, cSt	D 445	46.5	100.8	151.1	220.5	318.8
Viscosity Index	D 2270	104	98	96	96	95
Flash Point, °C	D 92	206	230	242	256	266
Pour Point, °C	D 97	-18	-12	-9	-9	-6
Density @ 15°C, Kg/l	D 1298	0.877	0.886	0.893	0.898	0.901
Rust Test	D 665A/B	Pass	Pass	Pass	Pass	Pass
Demulsibility, 54 oC Oil-Water-Emulsion, ml (60 minutes)	D 1401	0-0-80	0-0-80	0-0-80	0-0-80	0-0-80
Tackiness		Yes	Yes	Yes	Yes	Yes

April 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.