



# Gulf Mould Oil T

## Concrete mould oil

### Product Description

**Gulf Mould Oil T** is light coloured, highly effective, ready-to-use concrete mould oil specially formulated to ensure clean concrete release from wood, metal and other composite forms. It contains a special mould releasing agent to prevent sticking of concrete on moulds and impart superior surface finish. It also minimises surface irregularities, reduces voids and provides corrosion protection for metal forms during brief period of outdoor storage. It is recommended for use with a wide variety of concrete materials used in the construction and precast industries and is applied to the mould by brushing or spraying as a thin layer.

### Features & Benefits

- Prevents sticking of concrete on moulds
- Imparts superior surface finish
- Protects metal forms against corrosion for a brief period of outdoor storage
- Eliminates the need for brushing or special cleaning procedures before reuse of forms
- Stable in storage and will not become rancid
- Does not impart colour to the concrete mould

### Applications

- Moulding of wide variety of concrete materials used in the construction and precast industries
- Manufacture of precast concrete panels, structural units and prestressed bridge beams
- All types of forms where use of mineral oil based release agent is recommended

Note: For best results, it should be applied on clean and dirt-free surfaces. Over spills must be removed.

### Specifications, Approvals & Typical Properties

Typical Properties		
Test Parameters	ASTM Method	Test Values
Viscosity @ 40 °C, cSt	D 445	2.8
Flash Point, °C	D 92	80
Density @ 15°C, Kg/l	D 1298	0.801

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.