



# Gulf No Rust C2

*Water displacing rust preventive forming oily greasy protective film*

## Product Description

**Gulf No Rust C2** is water displacing type rust preventive and leaves an oily greasy protective film. It is specifically designed to provide medium-term protection of spare parts, components and machined surfaces made of ferrous and non-ferrous metals including aluminium, copper and their alloys with improved coverage. It is blended from selected rust prevention components and solvent to provide excellent dewatering properties, effective protective film and fast drying capability.

## Features & Benefits

- Facilitates rapid removal of water or coolant from metal surfaces
- Effective fingerprint corrosion suppressant thus making the film resistant to handling
- Forms effective protective film against aggressive atmospheres
- Excellent spreading allowing them to be applied either by dipping or by spraying.
- Rapid drying assists in increasing process speed.

## Applications

- **Gulf No Rust C 2** is recommended for medium-term protection of precision metal components made of ferrous & non-ferrous metals including aluminium, copper & their alloys after machining, extrusion, galvanizing or degreasing/ washing processes.
- **Gulf No Rust C 2** is best applied by dipping but if such facilities are not available it can also be sprayed. However, all precautions applicable to solvent-based products should be observed.
- Brushing of the fluid can also be used but extra care must be taken to ensure that brush fibres or extraneous dirt/ particulates are not inadvertently introduced as they have negative impact on anti-corrosion performance.
- If needed, the protective film can be removed by wiping off with rags/waste soaked in kerosene/mineral turpentine or by alkaline degreasants or solvent degreasing methods.
- **NOTE :** **Gulf No Rust C2** is compatible with normal steel components and pipework prevalent in the construction of application systems. Care should be exercised with selection and use of seals and paints in contact with this product.

## Specifications, Approvals & Typical Properties

Meets the following Specifications		
ISO 6743-8 (1987): ISO-L-REE category		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Appearance	Visual	Thin Amber Fluid
Viscosity @ 20 °C, cSt	D 445	2.8
Flash Point, PMCC , °C	D 93	42
Pour Point, °C	D 97	-54
Density @ 15°C, Kg/l	D 1298	0.802
Coverage (m <sup>2</sup> /l)		60
Film thickness, microns		4
Salt Spray test, hours to fail	B 117	100+
Humidity cabinet, days to fail	D 1748	120+
Indoor Protection, months		9
Outdoor Protection, months		3

March 2010

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.