



Gulf PowerTrac 4T

Premium 4-Stroke Motorcycle Oil

Product Description

Gulf PowerTrac 4T series are premium 4-stroke motorcycle engine oil for latest high performance motorcycles. It provides excellent protection to engine, gearbox and wet clutch and ensures highest degree of reliability under all operating conditions. These oil meets the specifications of API SN and JASO MA2, and the requirements of leading global 4-stroke motorcycle manufacturers. These are available in four different viscometrics, viz SAE 10W-30 & 10W-50 in synthetic and SAE 10W-40 & 15W-50 in semi-synthetic.

Features & Benefits

- Superior thermo-oxidative stability minimizes deposits, sludge build-up and oil thickening for extended engine & oil life
- Controlled frictional properties helps eliminate clutch slippage to provide enhanced power to wheels, fuel economy and improved rideability benefits
- Exceptional antiwear properties protect engine and gear components leading to reduced maintenance costs
- Excellent shear stability & low temperature fluidity helps maintain optimum viscosity at extreme temperatures to ensure effective lubrication & wear protection
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

Applications

- Recommended for high performance 4-stroke motorcycles of leading global manufacturers in wide range of operating conditions

Specifications, Approvals & Typical Properties

Meets the following Specifications		10W-30	10W-40	10W-50	15W-50
API SN		X	X	X	X
JASO MA2		X	X	X	X
Typical Properties					
Test Parameters	ASTM Method	Typical Values			
Viscosity @ 100 °C, cSt	D 445	11.1	14.4	18.2	18.8
Viscosity Index	D 2270	142	145	159	145
Flash Point, °C	D 92	236	220	234	224
Pour Point, °C	D 97	-33	-36	-33	-33
TBN, mg KOH/g	D 2896	8.9	7.6	7.6	7.6
Density @ 15°C, Kg/l	D 1298	0.86	0.869	0.859	0.871
Sulphated Ash, %wt	D 874	1.0	0.82	0.82	0.82

September 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.