



Gulf Pride 2T Plus

Semi-Synthetic, Low Smoke 2-Stroke Motorcycle Oil

Product Description

Gulf Pride 2T Plus is a premium quality semi-synthetic lubricant specially developed for high powered 2-stroke air cooled gasoline engines fitted with oil-injection or premix systems. It is formulated from premium quality base stocks, synthetic base fluid and unique performance additives for exceptional engine protection, cleanliness and low smoke in 2-stroke motorcycle/ scooter engines even under severe operating conditions. The product exceeds the latest international specifications of JASO FD, ISO-L-EGD & API TC and the requirements of leading global 2-stroke motorcycle/ scooter manufacturers.

Features & Benefits

- Outstanding lubricity protects against piston scuffing and premature wear of engine components
- Advanced formulation provides excellent control against engine deposits, exhaust system blocking and extended engine life without power loss
- Low ash additive technology prevents pre-ignition and spark plug fouling
- Specially selected synthetic base fluid reduces visible exhaust smoke
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures

Applications

- Recommended for high-powered 2-stroke motorcycles/ scooters operating under different conditions
- Suitable for both oil-injection and premix lubrication systems; follow manufacturer's recommendations for oil to fuel ratio
- Suitable for air cooled 2-stroke gasoline engines used in all terrain vehicles, lawn mowers and other applications requiring oils of this quality
- Also recommended for applications specifying ISO-L-EGC/ JASO FC or lower category oils for superior performance

Specifications, Approvals & Typical Properties

Meets the following Specifications		
ISO-L-EGD		
API TC		
Has the following On File Status		
JASO FD		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D445	7.75
Flash Point, °C	D 93	85
Pour Point, °C	D 97	-15
TBN, mg KOH/g	D 2896	1.40
Density @ 15°C, Kg/l	D 1298	0.861
Sulphated Ash, %wt	D 874	0.14

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.