



Gulf Pride 4004

4-Cycle Outboard Engine Oil

Product Description

Gulf Pride 4004 10W-40 is a premium quality 4-cycle engine oil for modern high output gasoline powered, water cooled outboard, inboard/outboard and personal watercraft engines. It exceeds the performance requirements of National Marine Manufacturers Association's specification NMMA FC-W® (Four Cycle-Water specification). This high quality oil is designed for the harsh operating conditions of marine environment and it provides excellent lubrication and protection against wear, deposits and rust & corrosion.

Features & Benefits

- Exceptional shear stability provides protection against viscosity loss leading to superior wear protection of engines operating under high load/ high speed for extended period of time
- Active cleaning agents provide superior engine cleanliness
- Advanced rust inhibitors guard against rust & corrosion even in marine salt water environment
- Good Low temperature fluidity assists easy cold start

Applications

- Recommended for and meets the warranty requirements of the following modern high output gasoline powered 4-cycle water cooled engines requiring NMMA FC-W® quality oil.
 1. Outboard Motors: Honda®, Mercury®, Yamaha®, Johnson®/Evinrude®, Bombardier/BRP®, Suzuki®, Nissan®, Tohatsu®.
 2. Inboard/Outboard Motors: Mercruiser®, Volvo Penta®, OMC®, Chrysler® Marine, Crusader®, Marine Power®, Chevrolet®, Ford®.
 3. Personal Watercraft: Honda®, Yamaha®, Bombardier/BRP® (Sea-Doo®), Polaris®

Specifications, Approvals & Typical Properties

Meets the following Specifications		
NMMA FC-W ®		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	15.0
HTHS (after D 6278), cP	D 4683	4.20
Viscosity Index	D 2270	151
Flash Point, °C	ISO 2592	226
Pour Point, °C	D 97	-30
TBN, mg KOH/g	D 2896	6.3
Density @ 15°C, Kg/l	D 1298	0.867
Sulphated Ash, %wt	D 874	0.84

December 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.