



Gulf Snowmobile 2T Syn

Synthetic, Low Smoke 2-Stroke Snowmobile Oil

Product Description

Gulf Snowmobile 2T Syn is a supreme performance synthetic lubricant specially developed for high output air cooled 2-stroke gasoline engines. Its unique formulation based on synthetic base fluids and advanced performance additives ensures excellent engine protection, cleanliness and low smoke even under extreme operating conditions. The product exceeds the latest international specifications of JASO FD, ISO-L-EGD & API TC and the requirements of leading global 2-stroke snowmobiles.

Features & Benefits

- Exceptional lubricity safeguards against piston scuffing and wear of engine components
- Advanced formulation provides exceptional control against engine deposits, exhaust system blocking and extended engine life without power loss
- Specially selected synthetic base fluid reduces visible exhaust smoke
- Low ash additive technology prevents pre-ignition and spark plug
- Excellent low temperature properties making it suitable for extreme cold weather conditions
- Easy miscibility with gasoline ensure stable homogeneous mixture even at low ambient temperatures

Applications

- Recommended for high-powered 2-stroke snowmobiles operating under different conditions.
- Suitable for oil-injection and premix lubrication systems; follow manufacturer's recommendations for oil-fuel ratio
- Suitable for high performance 2-stroke engines in all terrain vehicles, lawn mowers and other variety of applications requiring oils of this quality
- Also recommended for applications like motorcycles/ scooters specifying ISO-L-EGC/ JASO FC or lower category oils for superior performance

Specifications, Approvals & Typical Properties

Meets the following Specifications		
API TC		
JASO FD		
ISO-L-EGD		
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	10.9
Flash Point, °C	D 93	92
Pour Point, °C	D 97	-42
TBN, mg KOH/g	D 2896	1.6
Density @ 15°C, Kg/l	D 1298	0.864
Sulphated Ash, %wt	D 874	0.13

October 2009

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.