



Gulf Super Tractor Oil Universal

High performance multi-functional STOU

lubricant for farm equipment

Product Description

Gulf Super Tractor Oil Universal series are multifunctional tractor lubricants designed for use in a wide variety of modern farm equipment. These oils are blended from specially selected base stocks and advanced additive package to provide reliable performance in wide range of farming applications. These high performance STOU oils are suitable for use in diesel/gasoline engines, conventional gear drives, powershift transmissions, hydrostatic transmissions, hydraulics, final drives, power steering systems and oil-immersed brakes operating in agricultural services. These oils are available in SAE 10W-30, 10W-40, 15W-30, 15W-40 grades to enable the users to select an appropriate viscosity grade as recommended by farm equipment manufacturers for optimum performance.

Features & Benefits

- Multifunctional capability of these oils makes them suitable for most lubricant applications in farm equipment and reduces inventory and chances of misapplication
- Good thermo-oxidative stability and effective detergency/dispersancy controls sludge build-up and deposits leading to cleaner engines
- Protects gears, transmissions and bearings against wear, scuffing and pitting
- Ensures smooth (jerk free) hydraulic operation
- Excellent anticorrosion property protects all working components
- Good low temperature property ensures less wear and improved hydraulic response at cold start-up

Applications

- Suitable for most of the diesel/gasoline engines and transmission/hydraulic systems of tractors and other farm equipment
- Also suitable for other applications of farm equipment including oil immersed brakes, powershift transmissions, hydrostatic transmissions, power steering systems and conventional gear drives

Specifications, Approvals & Typical Properties

Recommended for applications requiring following Specifications	10W-30	10W-40	15W-30	15W-40	
API CF-4, CE, CF, SF	X	X	X	X	
API GL-4	X	X	X	X	
Massey Ferguson MF 1145		X	X	X	
Massey Ferguson MF 1144	X	X	X	X	
Massey Ferguson MF 1139	X		X		
John Deere J 27C	X			X	
Ford M2C 159B	X		X		
Allison C-4, ZF TE ML 06B, 07B	X	X	X	X	
Has the following Approvals					
Massey Ferguson MF 1145	X				
Typical Properties					
Test Parameters	ASTM Method	Typical Values			
Viscosity @ 100 °C, cSt	D 445	10.5	14.1	10.9	14.5
Viscosity Index	D 2270	139	150	125	138
Flash Point, °C	D 92	220	230	226	232
Pour Point, °C	D 97	-36	-36	-33	-33
TBN, mg KOH/g	D 2896	9.5	9.5	9.5	9.5
Density @ 15°C, Kg/l	D 1298	0.8821	0.8763	0.8886	0.8868

July 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.