



Gulf Superfleet

Commercial Vehicle Engine Oil

Product Description

Gulf Superfleet series are high performance diesel engine oils for use in turbocharged and naturally aspirated diesel engines operating under severe conditions. It is formulated from high quality base stocks and proven performance additives to provide excellent performance and engine protection under all types of operating conditions. The product meets the performance requirements of a wide range of diesel engines used in variety of applications.

Features & Benefits

- Improved thermo-oxidative stability controls sludge build-up and deposits
- Better detergency reduces deposits and keeps engines cleaner
- Good dispersancy helps in controlling soot related oil thickening and wear
- Effective antiwear properties protect critical engine parts
- Stay in grade shear stability leads to reduced oil consumption and wear

Applications

- Turbocharged and naturally aspirated diesel engines of all major global engine manufacturers meeting Euro I emission norms
- On-highway light and heavy duty trucking including high speed-high load service and short haul pick-up/delivery van
- Heavy duty diesel engines used in mining, construction, agriculture and other off-highway applications

Specifications, Approvals & Typical Properties

Meets the following Specifications		15W-40
API CF-4 , MB 228.1H, MTU Oil Category 1		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity at 100 °C, cSt	D 445	14.20
Viscosity Index	D 2270	140
Flash Point, °C	D 92	230
Pour Point, °C	D 97	-27
TBN, mg KOH/g	D 2896	7.6
Density @ 15°C, Kg/l	D 1298	0.894
Sulphated Ash, wt%	D 874	1.05

April 2022

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.