



Gulf Syngear LD

Synthetic Transmission Oil

Product Description

Gulf Syngear LD 75W-90 is a synthetic thermally stable gear lubricant designed to meet the demanding requirements of light-duty and heavy-duty commercial vehicles and off-highway equipment operating in most severe operating conditions. Blended from selected high quality base oils and Towproof™ additive technology, it offers exceptional load-carrying capability to provide reliable lubrication in applications encountering extreme pressure and shock loading. It offers unmatched protection for extended durability of driveline components and enhanced fuel efficiency.

Features & Benefits

- Exceptional load-carrying capability protects against wear in different operating conditions, enhances equipment durability and reduces maintenance costs
- Outstanding thermo-oxidative stability minimises deposits to provide longer aggregate life and extended oil drain intervals
- Effective low-temperature fluidity reduces wear and provides easy start-up under low ambient temperatures
- Excellent seal compatibility helps minimise leakages and reduce chances of contamination

Application

- Heavy duty hypoid type axles and final drives where such type of product is recommended.
- On-road light and heavy-duty trucks, buses and vans
- Off-highway equipment in construction, mining and agriculture
- Other heavy-duty applications involving hypoid and other gears operating under severe conditions like high speed/shock load, high speed/low torque and/or low speed/high torque

Specifications, Approvals & Typical Properties

Meets the following Specifications		75W-90
API GL-5		X
DTFR 12B140 (Previously known as MB 235.8)		X
Has the following Approvals		
Approval by PRI (SAE J2360 qualified product)		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity at 100 °C, cSt	D 445	15.0
Viscosity Index	D 2270	167
Flash Point, °C	D 92	205
Pour Point, °C	D 97	-42
Density @ 15°C, kg/l	D 1298	0.8619

GOLIL - December 2024

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.

www.gulfoilltd.com