



Gulf Syntrac 4T

Advanced Full Synthetic 4-Stroke Motorcycle Oil

Product Description

Gulf Syntrac 4T series are advanced full synthetic, 4-stroke motorcycle oil developed to meet the demanding requirements of 4-stroke gasoline engines in high performance motorcycles. It exceeds the most demanding lubrication requirements of modern 4-stroke motorcycles. It provides excellent protection to engine, gearbox and wet clutch over wide range of ambient temperatures and severe operating conditions to ensure high reliability. These oils meet the specifications of API SN, JASO MA2 and the requirements of leading global 4-stroke motorcycle manufacturers.

Features & Benefits

- Excellent thermo-oxidative stability minimises deposits and controls oil thickening facilitating extended engine and oil life
- Exceptional antiwear properties protect vital engine and gear components for reliable performance
- Controlled frictional properties minimize clutch slippage for enhanced power/ fuel economy and improves rideability
- Excellent shear stability maintains oil viscosity even under extreme conditions for consistent performance
- Outstanding low temperature properties enable easy start at low ambient temperatures and ensure effective lubrication and wear protection at start up
- Effective rust and corrosion inhibition property ensures longer life of critical engine components

Applications

- Recommended for advanced 4-stroke gasoline engines in high performance motorcycles of leading global manufacturers operating in wide range of ambient temperatures

Specifications, Approvals & Typical Properties

Meets the following Specifications	5W-40	10W-40	
API SN	X	X	
JASO MA2		X	
Has the following On File Status			
JASO MA2 on-file registration	X		
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity @ 100 °C, cSt	D 445	14.2	14.3
Viscosity Index	D 2270	171	156
Flash Point, °C	D 92	236	240
Pour Point, °C	D 97	-39	-33
TBN, mg KOH/g	D 2896	7.2	7.2
Density @ 15°C, Kg/l	D 1298	0.852	0.858
Sulphated Ash, %wt	D 874	0.80	0.80

May 2023

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.