



Gulf TEC Supreme

Passenger Car Motor Oil

Product Description

Gulf TEC Supreme is the most advanced high performance semi-synthetic passenger car motor oils exclusively developed for latest generation passenger cars and light duty vehicles running on gasoline and diesel. The latest formulation technology used in this oil provides unmatched levels of overall lubrication for all types of vehicles, especially high output, turbocharged, supercharged multi valve fuel injected engines in passenger cars, SUVs, light vans & trucks.

Features & Benefits

- Specially selected blend of base oils and advanced additive technology provide excellent engine protection
- Exceptional thermo-oxidative stability minimises deposits & sludge build-up and controls oil thickening, thereby facilitating extended oil life
- Superior antiwear technology provides exceptional wear protection under all conditions
- Excellent low volatility characteristics reduce oil consumption and hydro-carbon pollution
- Active cleaning agents ensure maximum engine cleanliness
- Excellent low temperature fluidity ensures easy cold start and protects against wear at start-up

Applications

- Recommended for all latest, high performance gasoline and diesel engines in cars, SUVs, light vans & trucks, particularly those using recent technologies (multi-valve engines, turbo compressors, and high cylinder capacity) and the new direct injection diesel engines with or without common rail.
- Especially suited to city stop-and-go, heavy load and/or high-speed applications where the conventional oils fail to perform and where such quality oils are recommended.

Specifications, Approvals & Typical Properties

Meets the Following Specifications		10W-40
ACEA A3/B4		X
API SN		X
MB 229.3/ 229.1, VW 502 00, 505 00, Renault RN0700/ 0710		X
PSA B712300		X
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	13.4
Viscosity Index	D 2270	147
Flash Point, °C	D 92	232
Pour Point, °C	D 97	-33
TBN, mg KOH/g	D 2896	10.6
Density @ 15°C, Kg/l	D 1298	0.873
CCS, cP at -25oC	D 5293	6704
MRV, cP at -30oC	D 4684	25100
HTHS, cP	D 4683	3.6

October 2017

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.