

# Gulf ZIPP 4T Smart 4-Stroke Motorcycle Oil

### **Product Description**

**Gulf ZIPP 4T Smart** is a high quality 4-stroke engine oil developed to meet the requirements of 4-stroke motorcycles. It provides reliable protection to engine and gears while ensuring smooth clutch performance under different operating conditions. It meets the performance specifications of API SG and JASO MA2.

#### Features & Benefits

- Reliable antiwear properties protect engine and gear components to offer dependable performance
- Better detergency/ dispersancy helps keep engine cleaner for reduced maintenance costs
- Controlled frictional properties provides smooth clutch performance for improved rideability
- · Good thermo-oxidative stability ensures consistent oil performance throughout oil life
- Effective rust and corrosion inhibition property helps extend engine/ component life

## **Application**

- Recommended for air cooled 4-stroke motorcycle engines where an API SG and JASO MA2 or JASO MA quality oil
  is required
- Also suitable for small 4-stroke gasoline engines used in portable generators, pumps, garden machinery, hand held equipment and other applications

# Specifications, Approvals & Typical Properties

| Meets the following Specifications |             | 20W-40 | 20W-50         |  |
|------------------------------------|-------------|--------|----------------|--|
| API SG                             |             | Х      | Х              |  |
| JASO MA2                           |             | Х      | Х              |  |
| Typical Properties                 |             |        |                |  |
| Test Parameters                    | ASTM Method | Туріса | Typical Values |  |
| Viscosity @ 100 °C, cSt            | D 445       | 13.7   | 18.0           |  |
| Viscosity Index                    | D 2270      | 107    | 123            |  |
| Flash Point, °C                    | D 92        | 240    | 246            |  |
| Pour Point, °C                     | D 97        | -24    | -24            |  |
| TBN, mg KOH/g                      | D 2896      | 4.5    | 4.5            |  |
| Density @ 15°C, Kg/l               | D 1298      | 0.878  | 0.878          |  |
| Sulphated Ash, %wt                 | D 874       | 0.66   | 0.66           |  |

GOLIL & GAP - November 2024