



Gulfo MA

High performance medium ash natural gas engine oils

Product Description

Gulfo MA series are high performance gas engine oils intended for use in highly-rated four-cycle spark ignited and “dual fuel” natural gas engines requiring “medium ash” oil or where “sour gas” is in use. They are specially developed to meet the requirements of the newer lean-burn engines and also to protect against wear and acid attack from the acidic materials generated during combustion. They are formulated from specially selected balanced package of additives to provide medium ash (0.9%), high TBN and low levels of phosphorus and zinc. The exceptional reserve alkalinity offsets the negative effects of corrosive materials on engine components and prevents corrosive wear in cylinders, valves and bearings resulting in longer engine life and lower maintenance costs. They exceed the performance requirements of API CF and are available in two viscosity grades viz. SAE 30 and SAE 40.

Features & Benefits

- Provides excellent engine cleanliness and improved performance
- Prevents corrosive wear in cylinders, valves and bearings resulting in longer engine life and lower maintenance costs
- High oxidation and nitration resistance makes these oils an excellent choice in many engines operating under high load and high temperature conditions
- Extended oil drain intervals and reduced oil filter costs
- Protects against valve seat recession
- Protects against wear and minimises ring scuffing of heavily loaded gas engines
- Minimises combustion chamber ash formation and improves spark plug performance
- Compatible with emission catalyst as it is formulated with less than 300 ppm phosphorus content

Applications

- Gas engines operating on fuel containing moderate levels of hydrogen sulphide (H₂S)
- Engines operating on fuel containing corrosive components such as TOHCL (Total Organic Halides as Chlorides), landfill or biomass gases
- “Dual-fuel” gas engines ignited by diesel pilot fuel
- Two-cycle and four-cycle gas engines that require medium ash oils
- Systems with catalytic converters used in both field pumping and cogeneration units
- Superior and lean-burn Waukesha engines

Specifications, Approvals & Typical Properties

SAE Viscosity Grade	30	40	
Meets the following Specifications			
API CF	X	X	
Typical Properties			
Test Parameters	ASTM Method	Typical Values	
Viscosity @ 100 °C, cSt	D 445	11.2	14.2
Viscosity Index	D 2270	98	97
Flash Point, °C	D 92	238	244
Pour Point, °C	D 97	-18	-15
Density @ 15°C, Kg/l	D 1298	0.873	0.878
Sulphated Ash, %wt	D 874	0.9	0.9
TBN, mg KOH/g	D 2896	8.6	8.6
Phosphorus, ppm	D 4927	< 300	< 300

Properties mentioned are typical only and minor variations, which do not affect product performance, are expected to arise in normal manufacturing processes. Please follow equipment manufacturer's recommendations for performance level and viscosity grade. The Safety Data Sheet for this product is available from your nearest Gulf Distributor. Please consult our local representative if any further information is required.

The information contained herein is believed to be correct at the time of publication and may be subject to modification from time to time. It is the user's responsibility to verify that this data sheet is current prior to using the product. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

This data sheet has been issued by us in English language only. In the event of any discrepancy between the English language version and any other language version, the English language version shall prevail.